

## PRODUCT DATA SHEET

### FX 4ST SL SAE 10W30

#### DESCRIPTION:

FX 4ST SL SAE 10W30 is a superior grade 4-stroke engine oil with advanced additive technology. This grade of engine oil is developed for modern 4 stroke Motorcycles & Scooters. It meets the international performance standards of API SL and JASO MA2 specification.

#### APPLICATION:

FLUX FX 4ST SL 10W30 is suited for four stroke scooters and motorcycles manufactured by Honda, Bajaj, TVS, Mahindra, Yamaha, Suzuki, which recommends the use of SAE 10W30 viscous material for fuel economy, particularly suitable latest generation gearless four stroke scooter.

#### PRODUCT BENEFITS:-

- Improves fuel efficiency and increases engine life.
- Ensure smooth clutch performance
- Specialized additives help to prevent build-up of harmful deposits

#### PERFORMANCE STANDARD:

FX 4ST SL SAE 10W30 meets the performance standard of API SL SAE 10W30/JASO MA2 specification

#### TYPICAL CHARACTERISTICS:

PRODUCT TYPICAL	TEST METHOD	UNITS	TYPICAL CHEMICAL ANALYSIS
<b>SAE Grade</b>			<b>10W-30</b>
Appearance			Bright & Clear
Colour			Golden
Kin. Viscosity @ 40°C,	ASTM D 445	cST	75 - 90
Kin. Viscosity @ 100°C,	ASTM D 445	cST	10.5 - 12
Viscosity Index, min.	ASTM D 2270	-	135
Flash Point, min.	ASTM D 92	°C	225
Pour Point, max.	ASTM D 97	°C	-30
TBN, min.		mg of KOH	8.5
Sulphated Ash % wt. max.	ASTM D874	%	1.0

Last update: 1<sup>st</sup> July, 2018

FLUX Lubricants, the FLUX Lubricants Logo and related marks are trademarks of RBM Lubricants, used under Licence.

This data sheet information contains is believed to be correct at time of publication. No warranty express or implied is made as to its accuracy or Completeness. Data provided is based on standard test under laboratory condition and gives as a guide only. These oils does not have possibility of significant health and safety hazard when they are used appropriately. RBM Lubricants takes no responsibility or liability for any damage or injury resulting from abnormal use of the product. For further information consult our technical representative.

Plant Address: RBM LUBRICANTS, Jayramdanga Khaskutti Road, P.O - Barbani, West Burdwan, West Bengal

EMAIL ID: [rbmlubricants@gmail.com](mailto:rbmlubricants@gmail.com)

[www.fluxlubricants.com](http://www.fluxlubricants.com)

