

PRODUCT DATA SHEET

FX 4ST SL SAE 20 W 50

DESCRIPTION:

FX PRIME SL SAE 20 W 50 is developed using synthetic blend, which reduces wear and maintains engine performance in a wide variety of driving condition. This oil protects from the start, dramatically reducing engine wear to keep it running smoothly.

APPLICATION:

FLUX FX PRIME SL 20W50 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends API SL/CF or earlier specification 20W-50 lubricant.

PRODUCT BENEFITS:

- Excellent start-up performance prevents sludge build up and controls oxidation
- Reduce oil volatility thus oil consumption
- Sustain improved performance for longer, even when under pressure

PERFORMANCE STANDARD:

FLUX FX PRIME SL 20W50 engine oil meets the API SL SAE 20W50 and JASO MA2 requirements.

TYPICAL CHARACTERISTICS:

PRODUCT TYPICAL	TEST METHOD	UNITS	TYPICAL CHEMICAL ANALYSIS
SAE Grade			20W-50
Appearance			Bright & Clear
Colour			Golden
Kin. Viscosity @ 40°C,	ASTM D 445	cST	135 – 145
Kin. Viscosity @ 100°C,	ASTM D 445	cST	17.5 – 18.5
Viscosity Index, min.	ASTM D 2270	-	120
Flash Point, min.	ASTM D 92	°C	230
Pour Point, max.	ASTM D 97	°C	- 21
TBN, min.		mg of KOH	7.0
Sulphated Ash % wt. max.	ASTM D874	%	1.0

Last update: 1st July, 2018

FLUX Lubricants, the FLUX Lubricants Logo and related marks are trademarks of RBM Lubricants, used under Licence.

This data sheet information contains is believed to be correct at time of publication. No warranty express or implied is made as to its accuracy or Completeness. Data provided is based on standard test under laboratory condition and gives as a guide only. These oils does not have possibility of significant health and safety hazard when they are used appropriately. RBM Lubricants takes no responsibility or liability for any damage or injury resulting from abnormal use of the product. For further information consult our technical representative.

Plant Address: RBM LUBRICANTS, Jayramdanga Khaskutti Road, P.O - Barbani, West Burdwan, West Bengal

EMAIL ID: rbmlubricants@gmail.com

www.fluxlubricants.com

