

PRODUCT DATA SHEET

FX PRIME CF4 15W40

DESCRIPTION:

FLUX FX PRIME CF4 15W40 is a premium quality, commercial multi grade heavy duty engine oil, developed to endure the most severe performance requirement of turbocharged & naturally aspirated diesel engines and gasoline engines more powerful and operating under stressful conditions. This oil is formulated with specialised additives in the oil provide protection against high temperature engine deposits, oil thickening and corrosion resistance. Its optimum viscosity characteristics resists drop in oil pressure, which result in greater power to engines.

APPLICATION:

FLUX FX PRIME CF4 15W40 high performance engine oil is suitable for mixed fleets of diesel engines (high speed, 4 strokes, turbocharged, or naturally aspirated, commercial road transport, small diesel engines, generator sets, etc.

PRODUCT BENEFITS:

- Broad viscosity range gives year round engine protection and performance
- Excellent thermal and oxidation stability helps keep engines clean for smoother operation
- Good corrosion resistance protects critical engine components
- Improve all round performance.

PERFORMANCE STANDARD:

FLUX FX PRIME CF4 15W40 meets performance level of API CF4/CD/SG SAE 15W40, MIL-L-20104E specification.

TYPICAL CHARACTERISTICS:

PRODUCT TYPICAL	TEST METHOD	UNITS	TYPICAL CHEMICAL ANALYSIS
SAE Grade			15W-40
Appearance			Bright & Clear
Colour			Golden
Kin. Viscosity @ 40°C,	ASTM D 445	cST	Report
Kin. Viscosity @ 100°C,	ASTM D 445	cST	14 - 15
Viscosity Index, min.	ASTM D 2270	-	125
Flash Point, min.	ASTM D 92	°C	220
Pour Point, max.	ASTM D 97	°C	-24
TBN, min.		mg of KOH	9

Last update: 1st July, 2018

FLUX Lubricants, the FLUX Lubricants Logo and related marks are trademarks of RBM Lubricants, used under Licence.

This data sheet information contains is believed to be correct at time of publication. No warranty express or implied is made as to its accuracy or Completeness. Data provided is based on standard test under laboratory condition and gives as a guide only. These oils does not have possibility of significant health and safety hazard when they are used appropriately. RBM Lubricants takes no responsibility or liability for any damage or injury resulting from abnormal use of the product. For further information consult our technical representative.

Plant Address: RBM LUBRICANTS, Jayramdanga Khaskutti Road, P.O – Barabani, West Burdwan, West Bengal

EMAIL ID: rbmlubricants@gmail.com

www.fluxlubricants.com

