

## PRODUCT DATA SHEET

### FX PRIME CF4 20W 40

#### DESCRIPTION:

FLUX FX PRIME CF4 20W40 is commercial multi grade premium performance heavy-duty diesel engine oil, formulated for both turbocharged & naturally aspirated diesel engines and gasoline engines of commercial vehicles – operating under severe & moderate conditions. The oil is readily compatible with most of the latest generation standard API CF4 oils commercially. This oil is suitable for all seasons and retains high level of alkalinity during use because of excellent protection against corrosive wear.

#### APPLICATION:

FLUX FX PRIME CF4 20W40 is suitable for all types of diesel and gasoline engines, TATA Motors, Ashok Leyland, Mahindra, Eicher, Force Motors, Escorts, Sonalika etc., commercial road transport, Agricultural Tractors, small diesel engines, generator sets etc.

#### PRODUCT BENEFITS:

- Good engine cleanliness
- Good protection from wear and deposits.
- Improved cold starting and faster engine warm up
- Lower fuel & engine oil consumption.

#### PERFORMANCE STANDARD:

FLUX FXPRIME CF4 20W40 meets the performance level of API CF4, CD, SG, MIL-L-46152E, ALLISON C-4, VOLVO VDS EDL4 of IS 13656:2014 specification

#### TYPICAL CHARACTERISTICS:

PRODUCT TYPICAL	TEST METHOD	UNITS	TYPICAL CHEMICAL ANALYSIS
<b>SAE Grade</b>			<b>20W-40</b>
Appearance			Bright & Clear
Colour			Red
Kin. Viscosity @ 40°C,	ASTM D 445	cST	Report
Kin. Viscosity @ 100°C,	ASTM D 445	cST	14 - 15
Viscosity Index, min.	ASTM D 2270	-	120
Flash Point, min.	ASTM D 92	°C	220
Pour Point, max.	ASTM D 97	°C	-21
TBN, min.		mg of KOH	9

Last update: 1<sup>st</sup> July, 2018

FLUX Lubricants, the FLUX Lubricants Logo and related marks are trademarks of RBM Lubricants, used under Licence.

This data sheet information contains is believed to be correct at time of publication. No warranty express or implied is made as to its accuracy or completeness. Data provided is based on standard test under laboratory condition and gives as a guide only. These oils does not have possibility of significant health and safety hazard when they are used appropriately. RBM Lubricants takes no responsibility or liability for any damage or injury resulting from abnormal use of the product. For further information consult our technical representative.

Plant Address: RBM LUBRICANTS, Jayramdanga Khaskutti Road, P.O – Barabani, West Burdwan, West Bengal

EMAIL ID: [rbmlubricants@gmail.com](mailto:rbmlubricants@gmail.com)

[www.fluxlubricants.com](http://www.fluxlubricants.com)

