

PRODUCT DATA SHEET

FX PRIME SAE 40

DESCRIPTION:

FX PRIME SAE 40 is commercial monograde diesel engine oils meeting API CF-4 specification. The specialised additives in the oil provide protection against high temperature engine deposits, oil degradation and corrosion resistance. The oil has excellent shear stability to maintain viscosity under severe, high operations.

APPLICATION:

FLUX FX PRIME SAE 40 is most suitable for diesel engines (High Speed, Four Stroke, Turbo Charged or naturally aspirated), commercial road transport, Tractors, High Speed engine in marine service (e.g. Fishing, River Transport etc.)

PRODUCT BENEFITS:

- Reduces engine scuffing and bore polishing
- Better engine protection and durability.
- Improved all round performance
- Good engine cleanliness.

PERFORMANCE STANDARD:

FLUX FX PRIME SAE 40 diesel engine oil meets the performance level of API CF/SF, Mack T8A, MIL 2104C standards.

TYPICAL CHARACTERISTICS:

PRODUCT TYPICAL	TEST METHOD	UNITS	TYPICAL CHEMICAL ANALYSIS
SAE Grade			40
Appearance			Bright & Clear
Colour			Golden
Kin. Viscosity @ 40°C,	ASTM D 445	cST	120 - 130
Kin. Viscosity @ 100°C,	ASTM D 445	cST	Report
Viscosity Index, min.	ASTM D 2270	-	110
Flash Point, min.	ASTM D 92	°C	220
Pour Point, max.	ASTM D 97	°C	-15

Last update: 1st July, 2018

FLUX Lubricants, the FLUX Lubricants Logo and related marks are trademarks of RBM Lubricants, used under Licence.

This data sheet information contains is believed to be correct at time of publication. No warranty express or implied is made as to its accuracy or completeness. Data provided is based on standard test under laboratory condition and gives as a guide only. These oils does not have possibility of significant health and safety hazard when they are used appropriately. RBM Lubricants takes no responsibility or liability for any damage or injury resulting from abnormal use of the product. For further information consult our technical representative.

Plant Address: RBM LUBRICANTS, Jayramdanga Khaskutti Road, P.O – Barabani, West Burdwan, West Bengal

EMAIL ID: rbmlubricants@gmail.com

www.fluxlubricants.com

