

PRODUCT DATA SHEET

FX AGRI 20W40

DESCRIPTION:

FLUX FX AGRI 20W40 is a high grade lubricant made from selected base oil high viscosity index and advanced additive technology, which increases the properties like antirust, anti-corrosion, low pour point to meets the lubrication requirements of Diesel Engines fitted on power tillers and agricultural pump sets.

APPLICATION:

FLUX FX AGRI 20W40 is ideal for all kind of agricultural pump sets and other stationary engines for industrial use; it is ideally suited for stop- start service found in power tillers.

PRODUCT BENEFITS:

- FLUX FX AGRI 20W40 allows pump running, smooth and trouble free for long periods at a stretch.
- Protects the engine and piston rings from corrosion and rust.
- Keeps the engine clean and provides long pump life.
- Keeps engine clean from sludge and hence reduces oil consumption.
- It is recommended for all types of diesel pump sets particularly where they work under continuous operations over prolonged interval of time.

PERFORMANCE STANDARD:

FLUX FX AGRI 20W40 meets the performance level of API CD/CF/CC SAE 20W40 specifications.

TYPICAL CHARACTERISTICS:

PRODUCT TYPICAL	TEST METHOD	UNITS	TYPICAL CHEMICAL ANALYSIS
SAE Grade			20W-40
Appearance			Bright & Clear
Colour			Red
Kin. Viscosity @ 40°C,	ASTM D 445	cST	Report
Kin. Viscosity @ 100°C,	ASTM D 445	cST	10.0 - 12.5
Viscosity Index, min.	ASTM D 2270	-	95
Flash Point	ASTM D 92	°C	220
Pour Point, max.	ASTM D 97	°C	-6
TBN, min.		mg of KOH	2
Sulphated Ash % wt. max.	ASTM D874	%	0.8

Last update: 1st July, 2018

FLUX Lubricants, the FLUX Lubricants Logo and related marks are trademarks of RBM Lubricants, used under Licence.

This data sheet information contains is believed to be correct at time of publication. No warranty express or implied is made as to its accuracy or Completeness. Data provided is based on standard test under laboratory condition and gives as a guide only. These oils does not have possibility of significant health and safety hazard when they are used appropriately. RBM Lubricants takes no responsibility or liability for any damage or injury resulting from abnormal use of the product. For further information consult our technical representative.

Plant Address: RBM LUBRICANTS, Jayramdanga Khaskutti Road, P.O – Barabani, West Burdwan, West Bengal

EMAIL ID: rbmlubricants@gmail.com

www.fluxlubricants.com

